

140 Series

Effluent Pumps

Effluent or dewatering submersible pump for septic tank, low pressure pipe (LPP), and enhanced flow STEP systems.

Features:

- Model 140: Non-clogging, engineered thermoplastic, vortex impeller; passes 1/2" (13 mm) spherical solids
- Model 145: Engineered thermoplastic, single vane impeller; passes 3/4" (19 mm) spherical solids
- 1-1/2" NPT vertical discharge
- Upper sleeve and lower ball bearing running in bath of oil
- Operates at 130 °F (54 °C) in effluent or dewatering applications
- Carbon/ceramic mechanical shaft seals
- Available in single and double shaft seal designs

Consult factory for special applications.

100% factory tested



Trusted. Tested. Tough.®


zoellerpumps.com 800-928-7867
3649 Cane Run Road, Louisville, KY 40211 USA



FM3158
1019
Supersedes
New

PRODUCT SPECIFICATIONS

MOTOR	Horse Power	3/4 - 1
	Voltage	115 or 230
	Phase	1 Ph
	Hertz	60 Hz
	RPM	3450
	Type	Permanent split capacitor
	Insulation	Class B
	Amps	6.0 - 13.0
PUMP	Operation	Automatic or nonautomatic
	Discharge Size	1-1/2" NPT
	Solids Handling	1/2" (12 mm), 3/4" (19 mm) spherical solids
	Cord Length	20' (6 m)
	Cord Type	UL listed, neoprene cord
	Max. Head	50' (15.2 m) or 74' (22.6 m)
	Max. Flow Rate	86 GPM (326 LPM) or 61 GPM (232 LPM)
	Max. Operating Temp.	130 °F (54 °C)
	Cooling	Oil filled
	Motor Protection	Auto reset thermal overload
	MATERIALS	Cap
Motor Housing		Cast iron
Pump Housing		Cast iron
Base		Cast iron
Upper Bearing		Sleeve bearing
Lower Bearing		Ball bearing
Mechanical Seals		Carbon and ceramic
Impeller Type		Single vane (145) or non-clogging vortex (140)
Impeller		Engineered thermoplastic
Hardware		Stainless steel
Motor Shaft		JIS S45C steel
Gasket		Neoprene



TOTAL DYNAMIC HEAD/FLOW PER MINUTE EFFLUENT AND DEWATERING

MODEL		140/4140		145/4145	
Feet	Meters	Gal.	Liters	Gal.	Liters
5	1.5	86	326	56	212
10	3.0	80	303	55	208
15	4.6	73	276	53	200
20	6.1	66	250	51	193
25	7.6	59	223	48	182
30	9.1	49	185	45	170
40	12.2	28	106	35	132
50	15.2	--	--	26	98
60	18.3	--	--	16	61
Shut-off Head:		50 ft.(15.2m)		74 ft.(22.6m)	